

DRYFIKS™ CRACK-SEAL10

(SHRINK FREE FILLER FOR PLASTER CRACK)

DESCRIPTION:

DRYFIKS™ CRACK-SEAL10 is made up of high-quality polymers, additives, and fillers. It is a putty-like substance that dries quickly and is used to patch fractures in plastered surfaces. It adheres firmly to cementitious substrates, is completely shrink-free, and is water-resistant once dried.

APPLICATION:

Internal & external surface cracks & plug holes on plaster up to 10 mm width.

CHARACTERISTICS / ADVANTAGES:

Shrinkageà Inhibits cohesive and adhesive failure upon exposure and does not shrink even after curing.

Applicationà Used as a one-time filler; unlike other acrylic crack filling paste, it doesn't need to be applied twice.

User friendlyà One pack of soft paste that is simple to apply using a putty knife.

Saggingà This non-sag nature aids in filling above and vertical fissures.

Sanding/polishingà Sanding is not necessary.

Stainingà stops any liquid substance from leaking onto the concrete surface, preventing staining.

Adhesionà Long-lasting durability on the applied surface and outstanding adherence to cementitious surfaces.

Paint-abilityà After 5–6 hours of treatment, it is easy to paint.

SURFACE PREPARATION:

- Dust, oil, grease, and other loose particles must be removed from the surface.
- Before applying **DRYFIKS™ CRACK-SEAL10**, wet the surface.
- No Shrink Fine hairline cracks need to be filled with **DRYFIKS™ CRACK-SEAL10** and enlarged to at least 1 mm.
- Painter's putty or POP must be removed until plaster surface is visible; internal surfaces should not shrink.

METHOD OF APPLICATION:

- Using a spatula or putty knife, press **DRYFIKS™ CRACK-SEAL10** firmly into the crack just once. Then, use palti patra to level the surface.
- Before painting, let it dry in the open for five to six hours to prevent cavities or bubbles from forming during application.
- After 48 hours of air curing, which is recommended for optimal results, POP or painter's putty can be applied.
- **Cleaning Instruction:** Use soap & water to clean tools & equipment. Use warm water & soap to wash hands.

RESTRICTIONS & CAUTION:

- Not appropriate for painter's putty or POP cracks.
- Avoid using it when it's raining or wet.
- The drying time will be prolonged if the application is below 10°C.
- After application, tightly seal the bottle.
- If the filler component gets too dry, mix 10 to 15 ml of potable water with 250 milliliters of **DRYFIKS™ CRACK-SEAL10**.

PROPERTIES:

Appearance	: Viscose paste
Color	: White
Base	: Acrylic with specially added fillers
Specific Gravity	: 1.06±0.02
Drying time@ 30°C	: 5-6 hrs.
Full curing time@ 30°C	: 48 hrs.
Coverage	: ~30-34 running m/ltr for a depth & width of 5 mm.
Shelf life	: 12 months from the date of mfg. Store in cool & dry place, away from sun light.

PACKAGING: 500g, 1kg, 5kg, 20kg & 50kg.

STORAGE AND SAFETY:

- Store in cool & dry place, away from sun light.
- With any chemical product, care should always be taken.
- Wearing protective gear, such as goggles and gloves, is advised (for specific recommendations, see the box and MSDS). Any skin or eye contact should be treated right away with fresh water.
- **DRYFIKS™ CRACK-SEAL10** have a shelf life of 12 months under packed & controlled storage warehouse condition.