

# DRYFIKS® BituArmor

*(Elastomeric Bitumen Emulsion Liquid Membrane for DPC coating & Roof coat)*

DRYFIKS™ BituArmor is a cold applied, water based bituminous emulsion for Damp proof coat and moisture vapor barrier coat for concrete application. It protects concrete structure from damage due to moisture and dampness.

## CHARACTERISTICS



Exhibits excellent flexibility and resists crack age.



Durable against UV radiation.



Resist water ingress into concrete



Low viscosity



Compatible with other paints & chemicals



Easy to apply via brush or roller.

## APPLICATIONS



Provides damp-proof protection for concrete



Act as a moisture resistant coating of concrete



Damp-proof protection for block structures.



Moisture resistant coating for bricks

## HOW TO APPLY

### Step 1: Surface Preparation

Ensure the surface is free from loose gravel, dirt.

Thoroughly cleanse the surface with high-pressure wash.

Before application, make sure that the surface is dry and clear.

### Step 2: Primer application

Apply a primer coat of the mixture of BituArmor with 25 % water on the surface

Evenly spread it with a brush or a roller.

### Step 3: Final application

Apply DRYFIKS® BituArmor by brush/roller on the primed surface at 0.25 L/m<sup>2</sup> as first coat

Allow first coat to dry and apply second coat of DRYFIKS® BituArmor at 0.25 L/m<sup>2</sup> in a perpendicular direction to the first.

Optional third coat can be applied after drying the previous coats.

## ADDITIONAL INFORMATION

1Kg of DRYFIKS® BituArmor covers 1.2-1.4 m<sup>2</sup> for primer and 2 coats of application  
Packs available: 5Kg, 20Kg

## PRECAUTIONS

- Drying time is 24 hours.
- Do not use below 5°C temperature or more than 87% of humidity.

