

GRIPFIKS GBA

(TEXTURED COAT ADHESIVE FOR MARBLE & GRANITE FOR CONSTRUCTION)

DESCRIPTION:

Autoflege provides high-performance construction chemical solutions, such as their **GRIPFIKS GBA**, which is marketed for its robust grip on rough marble & granite surface. GRIPFIKS GBA brand includes versatile bonding agents and polymer-based additives engineered to improve the structural integrity of tiles, stones, and concrete surfaces.

GRIPFIKS GBA is ready to use product for improving the adhesion of granite & marbles.

APPLICATION:

Superior Adhesion- Designed to ensure that granite, marble, stone cladding, and other heavy construction materials remain firmly bonded to substrates, even under stress or vibration.

Enhanced Water Resistance- formulations offer built-in moisture barriers, making them suitable for high-exposure areas like bathrooms, kitchens, and exterior walls.

Cost-Effectiveness- Autoflege positions their chemical range as a high-value alternative to traditional, high-cost market brands, providing comparable performance at a competitive price point.

CHARACTERISTICS / ADVANTAGES:

Using **GRIPFIKS GBA**, specialized bonding solutions offers several strategic benefits for contractors and developers looking to improve installation quality.

Structural Longevity: Prevents stone "pop-offs" and cracking caused by thermal expansion or structural vibration.

Superior Versatility: Compatible with granite, marble, and ceramic for both interior and exterior projects.

Economic Value: Delivers high-performance, professional-grade results at a competitive price.

Enhanced Site Efficiency: Simplifies preparation and application, reducing labor time and material waste.

Waterborne, non-toxic: Waterborne, non-toxic, and non-flammable formulation improves site safety and cleaning ease.

Resists Impregnation: Resists water impregnation to prevent deep-set moisture damage and staining.

SURFACE PREPARATION:

To ensure a secure, long-lasting installation, the substrate must be clean, sound, and properly conditioned.

Thorough Cleaning: Remove all loose particles, dust, grease, oil, paint, or laitance from the substrate surface.

Surface Soundness: Inspect the surface for cracks or weak patches.

Surface Profiling: If the surface is extremely smooth or non-porous, use mechanical means such as sanding or light wire brushing to roughen it.

APPLICATION METHOD:

Apply: Use a paint roller or brush to apply a thin, firm, and even coat.

Distribute: Ensure uniform coverage across the prepared surface and wipe away excess material from edges.

Ensure Coverage: Maintain a continuous, unbroken film to provide consistent bonding.

Dry: Allow approximately 6-24 hours for the product to cure completely before proceeding.

Fixing: After drying, granite or marble can be fixed using cement mortar or a suitable adhesive.

Coverage approx. 40-60 Sq feet per kg per coat.

PACKAGING: 1kg, 5kg.

STORAGE: **GRIPFIKS GBA** have a shelf life of 6 months under packed & controlled storage warehouse condition.